

# MATERIAL SAFETY DATA SHEET

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### Product Identification

Product Name: Black Foam Primer  
Product Number: pails, drums, totes  
Chemical Name: Water-based acrylic primer  
CAS Number: Blend

### Company Identification

ERSystems - Elastomeric Roofing Systems, Inc  
6900 Bleck Dr  
Rockford, MN 55373 USA  
1-800-403-7747 (For product information)  
1-800-535-5053 Infotrac (For emergencies)

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

### COMPONENT LISTING:

<u>Chemical Name</u>	<u>Amount</u>	<u>CAS Number</u>
ETHYLENE GLYCOL	< 2.0 %	107-21-1

(See Section 8 for exposure guidelines)

(See Section 15 for regulatory information)

## 3. HAZARDS IDENTIFICATION

```

***** EMERGENCY OVERVIEW *****
*
* CAUTION
*
* Prolonged or repeated contact may cause skin or eye
* irritation. May be harmful if swallowed. Protect
* from freezing.
*
*****

```





(section 5 continued)

**EXTINGUISHING MEDIA:**

Water, carbon dioxide, foam or dry powder.

**FIRE & EXPLOSION HAZARDS:**

No known unusual hazards in a fire/explosion situation.

**FIRE FIGHTING INSTRUCTIONS:**

As in any fire, wear self-contained breathing apparatus pressure-demand MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES**

**SAFEGUARDS (PERSONNEL):**

Wear safety goggles. Wear appropriate personal protective equipment.

**INITIAL CONTAINMENT:**

Contain spilled material. Absorb spills with inert material.

**LARGE SPILLS PROCEDURE:**

Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container.

**7. HANDLING AND STORAGE**

**RECOMMENDED STORAGE TEMPERATURE**

Minimum: 15.6 C (60.1 F)  
Maximum: 26.7 C (80.1 F)

**SHELF LIFE: (in original, sealed containers)**

8 months @ 26.7 C

**HANDLING (PERSONNEL):**

Avoid prolonged or repeated contact with skin. Wash hands thoroughly after handling.

**HANDLING (PHYSICAL ASPECTS):**

Agitate containers before use. Keep from freezing. Keep out of reach of children.

**STORAGE PRECAUTIONS:**

Avoid extreme temperatures. Keep container closed when not in use. Store in a cool dry place.



## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### EYE / FACE PROTECTION REQUIREMENTS:

Wear safety glasses. A respiratory protection program that meets OSHA's 29 CFR 1910-134 and ANSI Z88-2 requirements must be followed whenever workplace conditions warrant a respirator's use.

### SKIN PROTECTION REQUIREMENTS:

Selection of specific items such as gloves, boots, apron or full-body suit will depend on operation. Wash hands thoroughly after handling.

### RESPIRATORY PROTECTION REQUIREMENTS:

When there is potential for airborne exposures in excess of applicable limits, wear NIOSH/MSHA approved respiratory protection.

### EXPOSURE GUIDELINES:

#### ETHYLENE GLYCOL

OSHA Ceiling Limit: 50 ppm, 125 mg/m<sup>3</sup>

## 9. PHYSICAL AND CHEMICAL PROPERTIES

FORM .....	Liquid
COLOR .....	Black
ODOR .....	Faint Odor
BOILING POINT .....	212 F
SOLUBILITY IN WATER .....	Miscible
SPECIFIC GRAVITY .....	1.5 (Water = 1)
MELTING/FREEZING POINT .....	32 F
PH .....	8.5 to 9.5
VISCOSITY .....	7,000 to 10,000 cps
VOLATILE ORGANIC COMPOUNDS (VOC) ...	0.13 lb/gallon

## 10. STABILITY AND REACTIVITY

### STABILITY:

Stable.

### POLYMERIZATION:

Product will not undergo polymerization.

### DECOMPOSITION:

Decomposition will not occur if handled and stored properly.



## 11. TOXICOLOGICAL INFORMATION

No information available.

## 12. ECOLOGICAL INFORMATION

No information available.

## 13. DISPOSAL CONSIDERATIONS

### WASTE DISPOSAL:

Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.

## 14. TRANSPORTATION INFORMATION

PRODUCT LABEL .....: Black Foam Primer  
D.O.T. SHIPPING NAME ...: N/A  
D.O.T. HAZARD CLASS ....: Non-Hazardous

## 15. REGULATORY INFORMATION

### Canadian Disclosure List

ETHYLENE GLYCOL (107-21-1)

### SARA Title III - Section 313

ETHYLENE GLYCOL (107-21-1)

### Title V

ETHYLENE GLYCOL (107-21-1)

### SC Toxic Air Pollutants List

ETHYLENE GLYCOL (107-21-1)



**16. OTHER INFORMATION**

PREPARED BY .....: Laura Vollenweider  
APPROVED BY .....: Laura Vollenweider  
TITLE .....: Chemist  
APPROVAL DATE .....: July 31, 2003  
SUPERCEDES DATE ...: New  
MSDS NUMBER .....: CTGO00PRM0002  
RTN NUMBER .....: 00000021 (Official Copy)

**ADDITIONAL INFORMATION:**

The data in this Material Safety Data Sheet relates only to the specific material designated herein.

\*\*\*\*\*  
To the best of our knowledge, the information contained in this MSDS is accurate. It is intended to assist the user in his evaluation of the product's hazards, and safety precautions to be taken in its use. The data in this MSDS relate only to the specific material designated herein. We do not assume liability for the use of, or reliance on this information, nor do we guarantee its accuracy or completeness.

\*\*\*\*\*  
**END OF MSDS**  
\*\*\*\*\*

