



Elastomeric Roofing Systems, Inc

6900 Bleck Dr. Rockford, MN 55373
800.403.7747 -or- 763.565.6900 fax: 763.565.6901

ERSYSTEMS.COM

email: ersinfo@ersystems.com

EraPerm Clear Siliconized Wall Coating Product Data Specification

TYPICAL PHYSICAL PROPERTIES

Viscosity	1,000 cps
Moisture Vapor Permeance	80 perms
Weight/Gallon	8.2 Lbs
Fungi Resistance	Zero Rating
Shelf Stability	8 months
Cure Time	2-6 hours to recoat

DESCRIPTION

EraPerm Clear is an extremely breathable coating designed for masonry and other mineral based facades. Because EraPerm Clear is siliconized, it exhibits superior weatherability, excellent resistance to biological attack, high water repellency, low water absorption and tenacious adhesion.

USES

EraPerm Clear siliconized wall coating is designed specifically for use over mineral based surfaces. These may include: concrete, stucco, masonry and EIFS façade systems.

PACKAGING

Packaging is standard 5 gallons pails and 55 gallon drums.

APPLICATION

Coverage:

~150 square feet/gallon (Actual coverage will depend on the surface texture of the substrate. Each coat should be applied just to the point of running.)

Surface Preparation:

- All surfaces must be clean, dry and free of grease, oil and form release agents.
- Painted surfaces should be coated with EraPerm Coating (tinted). Perform adhesion tests to confirm performance.
- Clean surfaces using pressure wash, grinding, or wire brush.
- Cracks greater than 1/64 should be filled using clear, paintable, weatherproofing sealant.

Technique & Equipment:

EraPerm Clear can be applied by brush, roller or airless spray. Never apply in fewer than two coats. When using airless spray, always backroll the first coat.

Excellent results can be achieved with wet on wet application.

TEMPERATURE CONSTRAINTS

Do not apply EraPerm below 40° F. or in weather conditions where the temperature will fall below 40° F. during the cure cycle. The substrate temperature range for application is 40°F – 120°F.

CLEAN-UP

Flush all hoses, equipment, and tools with water immediately after use.

STORAGE

Always store EraPerm above 40° F. Keep from freezing!

CAUTION!!!!

Avoid prolonged and repeated contact with skin. Do not take internally.

Protect glass from EraPerm Clear, EraPerm Prime and EraPerm Siliconized wall coatings.

WARRANTY

IMPORTANT: While the information and data contained herein are presented in good faith and believed to be reliable, they do not constitute part of our terms and conditions of sale. Nothing herein shall be deemed to constitute a warranty, expressed or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

ERSystems' sole warranty is that the product will meet the sales specification at the time of shipment. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

PRIOR TO USE OF THIS MATERIAL, READ ALL APPROPRIATE MATERIAL SAFETY DATA SHEETS.