



Elastomeric Roofing Systems, Inc

6900 Bleck Dr. Rockford, MN 55373
800.403.7747 -or- 763.565.6900 fax: 763.565.6901

ERSYSTEMS.COM

email: ersinfo@ersystems.com

Fabric Faced Butyl Tape

Product Data Specification

TYPICAL PHYSICAL PROPERTIES

Base	Cured butyl rubber
Color	Black
Permiability	0.6
Low Temperature Flexibility	< - 50°F

DESCRIPTION & USES

Fabric Faced Butyl Tape is designed for repair and restoration of EPDM and other single ply membranes with failing or weak seams. It has excellent strength, adhesion and resistance to water.

PACKAGING

Roll Size: 6" x 250'

APPLICATION

(See Single Ply Roof Restoration Specifications)

Surfaces must be clean and dry. Single ply membranes should be primed (primer activator) prior to applying the tape.

Fabric Faced Butyl Tape should be cut to the desired length. The release liner then is peeled off the back and the tape is pressed into place along the seam. The tape is best positioned by hand, exercising care to remove bubbles and wrinkles and achieving a complete bond to the membrane surface.

LIMITATION

Avoid stretching during installation.

Store indoors, out of direct sunlight between 60 and 80°F.

WARRANTY

IMPORTANT: While the information and data contained herein are presented in good faith and believed to be reliable, they do not constitute part of our terms and conditions of sale. Nothing herein shall be deemed to constitute a warranty, expressed or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

ERSystems' sole warranty is that the product will meet the sales specification at the time of shipment. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

PRIOR TO USE OF THIS MATERIAL, READ ALL APPROPRIATE MATERIAL SAFETY DATA SHEETS.