



Elastomeric Roofing Systems, Inc

6900 Bleck Dr. Rockford, MN 55373

800.403.7747 -or- 763.565.6900 fax: 763.565.6901

ERSYSTEMS.COM

email: ersinfo@ersystems.com

Permaweld TPO Cover Tape

Product Data Specification

TYPICAL PHYSICAL PROPERTIES

Color	White
Cure State	Cured
Specific Gravity	.97
Overall Width	5"
Overall Thickness	.65"
Shelf Life	9 months

DESCRIPTION

ERSystems Permaweld TPO Cover Tape consists of a white tape adhesive that is laminated to a strip of Permaweld TPO membrane.

USES

Permaweld TPO Cover Tape is used for flashing gravel stops, covers for membrane fasteners, seam repair, reinforcing seals, patchings, etc. It sticks well to galvanized and painted steel, aluminum, most plastics, wood, brick, glass and smooth concrete.

SPECIAL CHARACTERISTICS

- Labor savings
- Quick tack from low to high temperature
- Cured product – long shelf life
- May be installed at sub-zero temperatures
- Contains no solvent

PACKAGING

Permaweld TPO Cover Tape is produced in 100 foot rolls using .35 inch thick Permaweld TPO laminated to .3 inches of tape adhesive, nominal. Two rolls to a box.

PREPARATION

Surface to be bonded must be clean and dry. For maximum performance the area to be spliced should be cleaned using Spice Wash and/or approved solvent and primed with ERSystems Permaweld TPO Bonding Adhesive.

Use Scotch Brite® scrub pads and/or clean rags to clean affected areas.

APPLICATION

Apply ERSystems Permaweld TPO Cover Tape per detailed instructions. For complete detailed instructions contact ERSystems Technical Department.

RECOMMENDED STORAGE

Store indoors and out of direct sunlight between 60°F and 80°F. This product will not degrade in normal warehouse storage, however the release paper may become difficult to remove. Shelf life is approximately 9 months. Shelf life will be shortened if exposed to elevated temperatures. Always rotate stock.

CAUTION!!!!

Cured Cover Tape contains ingredients which could be harmful if mishandled. Contact with skin and eyes should be avoided. Keep out of reach of children.

WARRANTY

IMPORTANT: While the information and data contained herein are presented in good faith and believed to be reliable, they do not constitute part of our terms and conditions of sale. Nothing herein shall be deemed to constitute a warranty, expressed or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

ERSystems' sole warranty is that the product will meet the sales specification at the time of shipment. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

PRIOR TO USE OF THIS MATERIAL, READ ALL APPROPRIATE MATERIAL SAFETY DATA SHEETS.

® Registered trademark of Minnesota Mining & Manufacturing Company.