



## Elastomeric Roofing Systems, Inc

6900 Bleck Dr. Rockford, MN 55373  
800.403.7747 -or- 763.565.6900 fax: 763.565.6901

[ERSYSTEMS.COM](http://ERSYSTEMS.COM)

email: [ersinfo@ersystems.com](mailto:ersinfo@ersystems.com)

## SPLICE WASH

### Product Data Specification

#### TYPICAL PHYSICAL PROPERTIES

Base	Solvent Blend
Color	Clear
Solids, %	0.00%
Viscosity, cps	Less than 50
Specific Gravity	0.768
Weight per Gallon	6.40 lbs.
Flash Point, °F. (TCC)	15°F
VOC (Max)	773 g/L

#### DESCRIPTION AND USES

ERSystems Splice Wash is designed for thorough cleaning of EPDM seams and splices prior to the application of primers or splice adhesives.

#### PACKAGING

Packaging is standard in 5 gallon pails.

DOT Label Required: Flammable Liquid

#### PREPARATION AND APPLICATION

Splice Wash should be applied with clean, lint-free rags. Change cleaning rags frequently.

#### COVERAGE

Approximate coverage is 200 lineal feet per gallon per 4" wide seam.

#### RECOMMENDED STORAGE

Store indoors, out of direct sunlight in original unopened containers between 60°F. and 80°F. Shelf life is approximately twelve months. Always rotate stock.

#### CAUTION!!!!

**FLAMMABLE!!** FOR PROFESSIONAL USE ONLY. Keep out of reach of children. Use only in well ventilated areas. Avoid prolonged contact with skin. Keep away from fire and open flames during storage and

use. Do not smoke while using.

#### WARRANTY

IMPORTANT: While the information and data contained herein are presented in good faith and believed to be reliable, they do not constitute part of our terms and conditions of sale. Nothing herein shall be deemed to constitute a warranty, expressed or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

ERSystems' sole warranty is that the product will meet the sales specification at the time of shipment. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

**PRIOR TO USE OF THIS MATERIAL, READ ALL APPROPRIATE MATERIAL SAFETY DATA SHEETS.**